

America's Leading Choice In Cleaning Machines for Pots, Pans & More!

Model FLC-36 Giant Capacity In A Front-Loading Machine



NSF

KEY FEATURES

- Large wash chamber accommodates standard delivery carts
- Rinse-line strainer
- Adjustable sanitary feet
- Special hose & nozzle for end-of-day cleanup (optional)
- Shipped to user fully assembled
- Factory wired & tested
- NSF certified

Ship Weight: 1,250 lbs.

Choose Alvey model FLC-36 washer for front-loading convenience and the capacity to accommodate standard delivery carts. This efficient stainless steel model also is ideal as a high-volume pot, pan and utensil washer. Completely automatic cycles subject objects being cleaned to a recirculated hot water-detergent spray wash, and a fresh-water sanitizing rinse.

SOLUTION (heat by these options)

- Steam injector
- Stainless steel heating coils
- Gas burner (natural or propane)
- Electric immersion heater

WASH CHAMBER

- 74"W x 30"D x 27"H
- Capacity: up to 36 sheet pans
- Accommodates 140-qt. mixing bowls
- Rotating spray-arm assemblies above & below wash area
- Stationary rinse nozzles located above & below wash area
- Removable pump cover for ease of maintenance
- Rinse water used to freshen wash medium

WASH PUMP

- 15 HP, TEFC motor
- Horizontally mounted pump
- Moves 240 GPM at 55 PSI
- Stainless steel wash & rinse piping
- Removable stainless steel wash nozzles
- Removable brass rinse nozzles
- Easily removable end caps for cleaning

TANK & HOUSING

- 14-gauge type-304 polished stainless construction
- All welded construction
- Stainless steel filter screens
- 50-gallon tank capacity

DOOR

- Vertical operation, stainless steel
- Counter-weighted for ease of operation
- Door-operated "off" switch for safety

CONTROL PANEL

- UL listed stainless steel panel
- Programmable cycles for light, medium and heavy soil conditions
- Automatic water fill
- Electronic temperature controller
- Digital temperature gauges
- 208v-, 230V- & 460V-3ph/60HZ available

Accessories & Optional Equipment For Model FLC-36

Rinse Water Booster Options

Steam Heated*

This unit equipped with: valve, steam strainer and steam trap (approx. wt.: 200 lbs.)

Electric Heated*

This unit equipped with: low-water cutoff, temperature-pressure relief valve, temperature-reducing valve and temperature-pressure gauge (approx. wt.: 200 lbs.)

Gas Heated*

This unit equipped with: gas-fired, computer-logic-controlled, high-efficiency heat exchanger (approx. wt.: 275 lbs.)

*** System will elevate temperature of incoming 120°F -140°F fresh water to 180°F**

Booster Mounting

Steam/Electric/Gas

Booster Floor Base

Steam

Optional Equipment For Model FLC-36

- Insulated Housing
- Draft Inducer (gas only)
- Work Tray
- Wash Hose & Nozzle
- Pressure Regulator (Steam)
- Pressure Regulator (Water)
- Booster Mounting
- Correctional Facility Application
- High-capacity Ventilation Fan
- In-line Water Softening System
- Hold-down Screens



ALVEY WASHING EQUIPMENT

11337 Williamson Road
Cincinnati, OH 45241
513-489-3060
FAX: 513-489-6018
www.afindustries.com

email: alveysales@afindustries.com

Racks & Baskets For Model FLC-36



- RO1078**
12-Pocket Bun Pan Rack



- B18311**
Utensil Basket with Lid

Items Not Pictured

- RO1035**
Steam Table Insert Rack
- B18320**
Miscellaneous Pan Basket with Lid
- WT0001**
Work Tray
- RO1042**
Cake & Pie Pan Rack
- Custom Racks Available**