

America's Leading Choice In Cleaning Machines for Pots, Pans & More!

Model KS-48 Roll-In Convenience, Superior Quality

Choose Alvey model KS-48 washer for roll-in convenience. This stainless steel cabinet-type washer is designed to clean racks, carts and delivery cabinets. Also, the KS-48 model is an efficient high-volume pot, pan and utensil washer.*



NSF

KEY FEATURES

- Floor or pit mountable
- Special hose & nozzle for end-of-day cleanup (optional)
- Easy-access drain valve
- Safety guard rails
- Shipped to user fully assembled
- NSF certified

Ship Weight: 3,250 lbs.

SOLUTION (heat by these options)

- Steam injector
- Stainless steel steam heating coils
- Gas burner (natural or propane)
- Electric immersion heater

WASH CHAMBER

- Accommodates racks 36"L x 28"W x 69"H
- Capacity: 48 sheet pans
- Four rotating spray assemblies
- Stationary rinse arms on each side
- Rinse water used to freshen wash medium

WASH PUMP

- 15 HP, TEFC motor
- Vertically mounted pump
- Moves 240 GPM at 55 PSI
- Stainless steel wash piping and nozzles
- Pump protection screen

TANK & HOUSING

- 14-gauge polished stainless construction
- All welded construction
- Stainless steel filter screens
- Stainless steel floor
- 67-gallon tank capacity

DOOR

- 32-1/2" W x 76-3/4" H opening
- Safety release latch for opening from inside
- Door-operated "off" switch for safety
- Drip-off area
- Triple-hung (3 hinges) door for added reliability

CONTROL PANEL

- UL listed stainless steel panel
- Programmable cycles for light, medium and heavy soil conditions
- Automatic water fill
- Electronic temperature controller
- Digital wash & rinse temperature indicators
- Wash & rinse pressure gauges
- 208V-, 230V- & 460V-3ph/60HZ available

* Optional racks available for this use

Accessories & Optional Equipment For Model KS-48

Rinse Water Booster Options

- Steam Heated***
This unit equipped with: valve, steam strainer and steam trap (approx. wt.: 200 lbs.)
 - Electric Heated***
This unit equipped with: low-water cutoff, temperature-pressure relief valve, temperature-reducing valve and temperature-pressure gauge (approx. wt.: 200 lbs.)
 - Gas Heated**
Available Upon Request
- * System will elevate temperature of incoming 120°F - 140°F fresh water to 180°F**
- Booster Mounting**
Steam/Electric
 - Booster Floor Base**
Steam

Optional Equipment For Model KS-48

- Insulated Housing** (priced on request)
- Draft Inducer**
- Automatic Drain**
- All Stainless Steel Wash/Rinse Piping**
- Pressure Regulator (Steam)**
- Pressure Regulator (Water)**
- Provisions for Monorail Operation**
- Over-sized & Custom-designed Units**
- 20HP Pump**
- Exhaust Fan** (Factory-wired with on/off switch located in control panel)



ALVEY WASHING EQUIPMENT
11337 Williamson Road
Cincinnati, OH 45241
513-489-3060
FAX: 513-489-6018
www.afindustries.com
email: alveysales@afindustries.com

Manufacturer reserves the right of modification without any prior notice

Racks & Baskets For Model KS-48



- RO1022**
Baskets for Pans to 3-1/2 inches



- RO1024**
Bucket/Bowl Cart



- RO1080**
Shelf-type Bun Pan Cart

Items Not Pictured

- RO1025**
Baskets for Pans to 8-1/2 inches
- B18354***
Utinsel Basket with Lid (fits in 8-1/2" basket)

* B18354 requires a RO1025 or RO1013