



SL-2S - Shown with optional 3rd door

#### HEATING OPTIONS

- Stainless steel steam heated coils
- Steam injector
- Electric immersion heaters

#### WASH CHAMBER SECTION

- 27" wide x 30-1/2" deep x 28" high
- Holds up to 12 18" x 26" sheet pans
- Holds 140 quart mixing bowl
- Rotating spray arms with stainless steel nozzles located above and below wash tray
- Stationary rinse nozzles located above and below wash tray

#### WASH PUMP

- 10 HP totally enclosed, fan cooled motor, horizontally mounted pump
- 240 G.P.M. at 45 PSI
- Stainless steel wash and rinse piping
- The wash spray arms are provided with easily removable nozzles and end caps for maintenance and cleaning
- Removable stainless steel cover panel for easy maintenance and cleaning

## MODEL SL-2S

### Pass Through Operation

The Alvey Model SL-2S is a compact, completely automatic, stainless steel, two-door pass through machine. The wash cycle consists of a recirculated hot detergent wash followed by a fresh water rinse.

Options listed on back.

- 208V    230V    460V



#### This machine is used to clean:

Pots, trays, dishes, pans, large bowls.

#### Common places this machine is used:

Bakeries, institutions, correctional facilities

#### TANK AND HOUSING

- Constructed of all welded 14 gauge type 304 stainless steel with polished finish
- 30 gallon capacity
- Stainless steel filter screens
- Drain valve with overflow

#### DOOR

- Vertical opening/stainless steel
- Counter weighted for easy operation
- Door operated safety switch

#### CONTROL PANEL

- UL listed stainless steel panel
- Programmable cycles for light, medium and heavy soil conditions
- Automatic water fill
- Electronic temperature control
- Digital temperature gauges

#### FEATURES

- NSF Certified
- Wash and rinse pressure gauges
- Rinse line strainer
- Adjustable sanitary feet
- Wash grate tray
- Automatic hold-down grid for light items

Shipping Wt. 1200 Lbs.

## Accessories & Optional Equipment for Model SL-2S

### Booster Options for Rinse Water

#### Steam Heated Rinse Water Booster

System will elevate rinse water temperature up to 180°. This unit comes equipped with Shutoff Valve, Steam Strainer, and Steam Trap. (approx. weight of 200lbs.)

#### Electric Heated Rinse Water Booster

System will elevate temperature of incoming rinse water to 180°. This unit is equipped with : temperature pressure relief valve, pressure reducing valve and temperature-pressure gauge (approx. 200lbs.)

#### Booster Mounting Options


- Top
- Floor

### Options for Model SL-2S

- Custom Designed Racks & Baskets
- Insulated Housing
- Third Door
- Corner Load
- Exhaust Fan
- Detergent Dispenser

### Racks & Baskets for Model SL-2S

- R01035 - Pocket Steam Table Insert Rack
- R01078 - 12 Pocket Bun Pan Rack
- B18311 - Utensil Basket with Lid
- B18320 - Miscellaneous Pan Basket with Lid



R01078



B18311



R01035